NEOVOLTA

All-In-One ESS

NV Wave

Energy Storage Reimaginged



Patented Modular Design

Click-in 2.4 - 9.6 kW Inverter

3.45 kWh - 55.2 kWh Capacity

LiFePO4 Lithium Iron Batteries

15 Year Warranty



NEOVOLTA

NV Wave

Performance

AC Voltage	120 / 240 Vac Split Phase
Frequency	60 Hz
Inverter Capacity	2.4; 4.8; 7.2; 9.6 kW
Pass Through Rating (A)	200
Off-Grid Capable	Yes
PORTABLE GENSET (optional)	Yes
Capacity	Single Enclosure: 3.45 - 13.8 kWh
	+ 1 Extension Unit: 17.25 - 34.5 kWh
	+ 2 Extension Units: 37.95 - 55.2 kWh
Chemistry	LFP (LiFePO4)
Performance Warranty	15 Years
Round Trip Efficiency	97.5%

Environmental

Maximum Temperature Range	-4° F to +131° F (Charging)
	-20° C to +55° C (Discharging)
Enclosure Type	Indoor and Outdoor (NEMA 3R)
Max Elevation	≤ 4,000m (10% derating when above 4000m/13,123ft)
Noise Level	- 45 dB

Connectivity


Bluetooth / APP / WIFI	Yes
Interface	CAN, R5485 Modbus
Monitoring	iOS, Android
Programmable Controls	Yes

Compliance

Safety (Pending UL Certification)


UL 9540, UL 9540A, UL 1642, UL 1973, UN 38.3, UL 1741, UL 1741SA, IEEE 1547, CA RULE 21, HECO

Single Line Diagram




Customizable Configuration

SINGLE CABINET



3.45 - 13.8 kWh

CABINET +1 EXTENSION UNIT



17.25 - 34.5 kWh

CABINET +2 EXTENSION UNITS



37.95 - 55.2 kWh



3.45 - 55.2 kWh

2.4 - 9.6 kW