

NEOVOLTA™



Hybrid Inverter

NV7600

Designed and Engineered in
California since 2018

Compact Design

On Grid and Off Grid

DC and AC Solar

Generator Ready

Stackable



800.364.5464
NEOVOLTA.COM

NV7600

PV String Input Data

Max. PV Input Power* (W)	11,400**
Max. PV Input Voltage (Voc)	500
Startup Voltage (Vmp)	125
MPPT Voltage Range (Vmp)	150-425
Rated PV Input Voltage Max. Operation	370
PV Input Current (A) @ MPPT	26 + 26
Max. Input Short-Circuit Current (A) @ MPPT	44 + 44
MPPT Strings per MPPT	2 2 + 2

*Max. PV Input Voltage of 500Voc shall be calculated at coldest operating temperature of installation locations.
 ** Inverter will self-limit to 11,400W of max combined solar input.

AC Input/Output Data

Rated AC Output (W/VA)	7,600/8360
Max. AC Solar or Generator Input	8,360
Rated AC Input/Output (A)	31.7
Max. AC Input/Output (A)	34.8
Max. Continuous AC Passthrough (grid to load) (A)	50
Peak Power (off-grid) (W)	2 times rated power (15,200W); 10s
Power Factor Adjustment Range	0.9 - 1.0
Rated Input/Output Voltage Voltage Range (V)	120/240; 208/3-Phase
Rated Input/Output Frequency Frequency Range (Hz)	60 55-65
Grid Connection Form	2L + N + PE
Total Current Harmonic Distortion (THDi)	<3% (of nominal power)
Max. Parallel for on-grid and off-grid*	4(pcs) 120/240Vac 3(pcs) 120/208Vac

*This is for inverter paralleling ONLY. NV7600 w/ NVPLUS is UL9540 listed for (4) inverters w/ (5) batteries

Battery Input Data (DC)

Battery Type (Compatible)	Lithium Iron Phosphate (LiFePO4)
Battery Voltage Range (V) Max.	40-60
Charging Current (A) Max.	190
Discharging Current (A) Charging	190
Strategy for Li-ion Battery	Self-Adoption BMS 1
Number of Battery Inputs	(2 wires; positive and negative)

Equipment

Integrated

Protection: DC Polarity Reverse Connection, AC Output Overcurrent, Thermal, AC Output Overvoltage, AC Output Short Circuit, Overvoltage Load Drop, Surge

Monitoring: DC Component, Ground Fault Current, Power Network, Island Protection, Earth Fault Detection, DC Input Switch, DC Terminal Insulation Impedance, Residual Current (RCD) Detection, Arc Fault Circuit Interrupter (optional)

Surge Protection	Type II (DC), TYPE II (AC)
Communication Interface	RS485 RS232 CAN
Monitor Mode	GRPS WiFi Bluetooth 4G LAN (optional)

General Data

Operating Temperature (°F / °C)	-40°F to 140°F / -40°C to 60°C
Humidity Limit (%)	0-100%
Max. Elevation	2000m/6561ft (10% derating at 3000m/9842ft)
Noise (dB)	<30
IP Rating	TYPE 3R
Typology	Non-Isolated
Overvoltage Category	OVC II (DC), OVC III (AC)
Dimensions (W x H x D) Weight (lbs)	16.5" x 26.4 x 9.2" 66
Cooling	Intelligent Air Cooling
Max. Efficiency (%)	97.6
MPPT Efficiency (%)	>99.0
Warranty Grid Regulation	15 years
Certifications	IEE1547.1 SRD V2.0 HECO UL1741 CRD UL1741 SB UL1699B CEC SGIP LUMA
Load Start Capability*	80A

*Load start capability may vary

Disclaimer: The information provided herein is correct to the best of NeoVolta's knowledge, is presented in good faith and believed to be correct at the time of printing. No liability for any errors, facts or opinions is accepted. In no event will NeoVolta be responsible for damages of any nature whatsoever resulting from the use of or reliance upon information from this specification sheet or the products to which the information refers. All weights and measures shown are best approximations.